



www.optilumen.com



Project Name	
Model Number	
Fixture Type	
Notes	

PRODUCT IDENTIFICATION

Product Model: LHB Series Highbay/Lowbay Product Description: 4' steel suspended fixture, w/90° mirror reflector, LED strips and drivers Product Applications: General Area and task lighting in warehousing, industrial, large retail, w/mounting heights of 12-45'

PRODUCT SPECIFICATIONS

Voltage: 100-277v, 50- 60 Hz Power Factor: .96/.998, 120v/277v Power Supplied: Quick-connect, remote driver THD: 3.11% @ 120v, 8.46% @ 277v Luminous Efficiency: 142 lm/w LED, 118-122 lm/w Luminaire CCT: 5000K CRI (Ra): >82

Model Number	Nominal Power	LED Modules	Net Lumens	Replaces	Dimensions
LHB80-55	80W	4 x 20w	10,100	320-400w MH	48"x11"x4"
LHB120-55	120W	2x20w + 2x40w	15,050	400-600w MH	48"x11"x4"
LHB160-55	160W	4x40w	20,100	500-750w MH	48"x11"x4"
LHB240-55	240W	6x40w	30,200	800-1200w MH	48"x16"x4"

The LHB series luminaire represents an incredibly efficient and cost effective solution for areas that have high lumen demand, and medium to high mounting heights. Multiple LED driver design allows convenient partial-power operation for daylight harvesting, occupancy sensing, etc., achieving even higher efficiency. 90° mirror reflector maintains accurate distribution of light. Installation options include surface mount, pendant mount or aircraft cable hanging kits. Quick disconnect whips are available in a variety of lengths, wire gauges, and plug styles.